











Panel PC

P10A


- Powered by 12th-generation Intel® Core™ i5-1235U/i7-1255U Processors, equipped with Windows 11 operating system
- 10.1-inch flat capacitive touch panel is impact-resistant, 700 nits high brightness screen
- Wi-Fi 6, Bluetooth 5.1, and expandable 4G (M.2 interface), multiple network connection modes
- Fanless design, using large-area uniform heating fin, running 24/7 without affecting reliability and service life
- Excellent environmental adaptability, anti-electromagnetic interference and anti-static capabilities
- Rich interfaces, including multiple USB/RJ45/DB9/HDMI and other I/O ports, easily meet various scenario requirements
- Wide voltage and temperature design, IP65-rated dustproof and waterproof
- Standard PPC mounting hook component, easy to install and supports various installation methods such as embedded and wall-mounted



| | | | | |
|---|---|---|---|---|
|  |  |  |  |  |
| i5-1235U/i7-1255U Processors | Windows 11 Operating System | 10.1 inch screen | 700cd/m ² Brightness | 800*1280 Screen resolution |
|  |  |  |  |  |
| WiFi 6 | Running 24/7 without affecting reliability | Rich interface extensions | storage expansion | IP65 |

Panel PC P10A

Specifications

 **CPU**
12th Generation Intel® Core™
i5-1235U Processor (Optional
i7-1255U)

 **Operating System**
Windows 11

 **Memory**
RAM: 8GB
ROM: 128GB (Optional
256/512GB)


 **Display**
Type: LCD
Size: 10.1 inch 16 :10
Resolution: 800×1280
Brightness:700 cd/m²

 **Touch Panel**
10 PCAP, G+G

 **Dimension/Weight**
257.2*170*45.95mm
1.2kg

 **Internet**
Optional 4G/WIFI6/BT5.1

 **Certification**
Front panel IP65

 **Rugged Features**
Working temperature: -20 °C
to 60 °C Storage temperature:
-30 °C to 70 °C Humidity: 95%
Non-Condensing

 **Adapter**
Input: 100~240V AC 50/60Hz
Output: 19V/3.42A

 **I/O Interface**
Type-A USB3.0*4
Power interface DC 19V *1 (Support
12--24V)
§ 3.5mm Standard Earphone Jack *1
RJ45 *2 (10M/100M/1000M adaptive)
DB9 PORT RS232 *2
HDMI *1
M2 *1 M.2 2280 standard
interface (Support SATAIII/PCIE3.0X4
signal)



* The technical specifications of this product are subject to change without prior notice