



M14M

Enterprise-Grade Rugged Tablet

- All-new Intel® Core™ Ultra processor, Windows 11 OS
- The newly added NPU, a dedicated AI acceleration engine
- Standard 32+256GB, Dual memory and dual storage slots
- 14-inch HD&HB screen. The back features a rotating handle
- 53.58Wh+14.4Wh dual batteries
- IP65 & MIL-STD-810H Certified



Durability	<ul style="list-style-type: none"> MIL-STD-810H certified IP65 certified 4ft, 26 drops (each side, edge, and corner) ±4kV contact discharge, ±8kV air discharge
Operating System	<ul style="list-style-type: none"> Windows 11 Pro Optional Windows 11 Home/IOT
Processor	<ul style="list-style-type: none"> Intel Ultra 7 155H (24MB cache, up to 4.8 GHz, 16 cores, 22 threads, TDP 28W) Optional Intel Ultra 5 125H (18MB cache, up to 4.5 GHz, 14 cores, 18 threads, TDP 28W)
Graphics	<ul style="list-style-type: none"> Intel Xe LPG Graphics
Memory	<ul style="list-style-type: none"> 32GB DDR5 SO-DIMM Optional 16GB DDR5
Storage	<ul style="list-style-type: none"> 256GB PCIe SSD Optional 512GB/1TB SSD
Display	<ul style="list-style-type: none"> 14.0", FHD (1920x1080), 1000 nits 10-point capacitive touch screen, supports glove touch mode
Audio	<ul style="list-style-type: none"> Integrated 3W speaker Integrated microphone Class K
Camera	<ul style="list-style-type: none"> MF 5.0 MP front camera AF 13.0 MP rear camera
Keyboard & Input	<ul style="list-style-type: none"> 6 buttons (user-definable key x2)
Network & Connectivity	<ul style="list-style-type: none"> Intel® Wi-Fi 6/Wi-Fi 6E (802.11 ax) Bluetooth® 5.1 4G LTE Optional 5G GPS module

Security	<ul style="list-style-type: none"> Integrated TPM2.0 Fingerprint scanner HF-RFID (NFC) reader
Data Capture	<ul style="list-style-type: none"> Optional 1D/2D barcode scanner
I/O Interface	<ul style="list-style-type: none"> Micro SD card x1 SIM card x1 USB 3.2 Gen 2 (Type-A) x1 Thunderbolt 4 (Type-C) x1 3.5 mm audio jack x1 HDMI 2.0a mini x1 10/100/1000M Ethernet (RJ45) x1 Fan x1 12-pin Pogo pin x1 (charge & USB) USB 2.0 (Type-A) x2 10/100/1000M Ethernet (RJ45) x1 Serial port (RS232: D-sub, 9-pin) x1 5.5 mm DC in jack x1
Expansion Module	<ul style="list-style-type: none"> Optional 2nd NVME PCIe SSD Optional user-definable PCIe module
Battery & Charging	<ul style="list-style-type: none"> Li-ion battery, 11.4V, 4700mAh, 8h Li-ion battery, 11.1V, 1300mAh Separate RTC 3V/210mAh AC adapter: 100-240V · 50Hz-60Hz · 71.82W (19V/3.78A)
Environment	<ul style="list-style-type: none"> Operating temperature: -20°C to 60°C (-4°F to 140°F) Storage temperature: -30°C to 70°C (-22°F to 158°F) Humidity: 95% (non-condensing)
Dimension	<ul style="list-style-type: none"> 366.2 mm(L) × 246.9 mm (W) × 24.8mm (H)
Weight	<ul style="list-style-type: none"> 2350g
Accessories	<ul style="list-style-type: none"> Standard: Adapter, Hand strap, Removable battery
Warranty	<ul style="list-style-type: none"> One-year limited warranty standard

1. Please contact your sales representative for feature availability.
2. Battery life data is provided by Emdoor's laboratory. Default test conditions: 300 nits display brightness, 30 cm/70 dB sound level. Actual results may vary depending on test environments and methods.
3. Certified to MIL-STD-810H and IP standards. For specific test items and methods, please refer to the latest official test report.
4. Body dimensions and weight are measured by Emdoor's laboratory. Variations may occur due to measurement methods and manufacturing processes.
5. All product images, specifications, user interface, and features are for reference only and may vary by production batch or other factors. All information is subject to change without prior notice.

ACCESSORIES

Optional



Adapter



Carry Handle



Removable Battery

CONTACT US

Shenzhen Emdoor Information Co., Ltd. (Stock Code: 001314)

Tel: (+86) 400-830-4882

Web: www.onerugged.com

Email: inquiry@onerugged.com

Address: Emdoor Building, No.8 Guangke 1st Road, Pingshan District, Shenzhen

