



T1

Outdoor Rugged Tablet

- 8.68" narrow-bezel HD display
- Helio G99 chip + Android 14 OS
- Powerful 8000mAh battery, 33W super fast charging
- 48MP rear camera + 32MP front camera
- WIFI 5/4G/BT5.2 multiple communications
- IP68 high protection level, 1.22m drop resistant



Durability	<ul style="list-style-type: none"> MIL-STD-810H certified 4ft drop 26 faces IP68 certified ±8kV contact discharge, ±12kV air discharge
Operating System	<ul style="list-style-type: none"> Android 14
Processor	<ul style="list-style-type: none"> MT8781 (6x 2.2Ghz Cortex-A76, 2x 2.0Ghz Cortex-A55)
Graphics	<ul style="list-style-type: none"> ARM G57 MC2
Memory	<ul style="list-style-type: none"> 8GB LPDDR4x on board
Storage	<ul style="list-style-type: none"> 128GB UFS2.2 Optional 256GB UFS2.2
Display	<ul style="list-style-type: none"> 8.68" FHD(800*1340), 400nits 10-point capacitive touchscreen, support Glove&Water
Audio	<ul style="list-style-type: none"> Integrated microphone Integrated 2W speaker x2 Smart PA
Camera	<ul style="list-style-type: none"> Integrated 32.0 MP front camera Integrated 48.0 MP rear camera
Keyboard & Input	<ul style="list-style-type: none"> 3 buttons
Network & Connectivity	<ul style="list-style-type: none"> Intel® Wi-Fi 5 (802.11 ac) Bluetooth® V5.2 Integrated 4G LTE multi-carrier mobile broadband LTE-FDD(B1/2/3/4/5/7/8/12/17/18/19/20//25/26/28A/28B/66) LTE-TDD(B34/38/39/40/41) WCDMA(B1/2/4/5/8) GSM(B2/3/5/8) Integrated GPS, Beidou, Galileo, Glonass module

Security	<ul style="list-style-type: none"> Integrated HF-RFID (NFC) reader
Data Capture	<ul style="list-style-type: none"> Support face unlocking
I/O Interface	<ul style="list-style-type: none"> USB2.0 (typeC) x1 2 of 3 card slot (Nano Sim+Micro SD or Nano Sim+Nano Sim)
Battery & Charging	<ul style="list-style-type: none"> Battery Li-Ion, 3.85V, 8000mAh, 11.2 hours 33W Type-C Adapter
Environment	<ul style="list-style-type: none"> Operating temperature: -20°C ~ 60°C (-4°F ~ 140°F) Storage temperature: -30°C ~ 70°C (-22°F-158°F) Humidity: 95% (Non-Condensing)
Dimension	<ul style="list-style-type: none"> 220.14 mm(L) × 135.5 mm(W) × 14 mm(H)
Weight	<ul style="list-style-type: none"> 569g
Accessories	<ul style="list-style-type: none"> Standard: Adapter, Cable(typeC), Hand Strap Optional: Film
Warranty	<ul style="list-style-type: none"> One-year limited warranty standard

1. Please contact your sales representative for feature availability.
 2. Battery life data is provided by Emdoor's laboratory. Default test conditions: 300 nits display brightness, 30 cm/70 dB sound level. Actual results may vary depending on test environments and methods.
 3. Certified to MIL-STD-810H and IP standards. For specific test items and methods, please refer to the latest official test report.
 4. Body dimensions and weight are measured by Emdoor's laboratory. Variations may occur due to measurement methods and manufacturing processes.
 5. All product images, specifications, user interface, and features are for reference only and may vary by production batch or other factors. All information is subject to change without prior notice.

ACCESSORIES

Standard



Adapter



Cable (Type-C)



Hand Strap

Optional



Film

CONTACT US

Shenzhen Emdoor Information Co., Ltd. (Stock Code: 001314)

Tel: +86-(0)755-2372 2880

Email: marketing.info@emdoor.com

Web: www.emdoorugged.com

Address: Emdoor Building, No.8 Guangke 1st Road, Pingshan District, Shenzhen

